




Shell Spirax S4 TXM

, SAE 10W-30,

(UTTO)"

S4 TXM

DESIGNED TO MEET CHALLENGES

- 가
- S4 TXM 가 가 가
- OEM S4 TXM
-  S4 TXM John Deere, Massey Ferguson, CNH ZF Shell LubaMatch
- S4 TXM S4 TXM 가
- S4 TXM 가 S4 TXM
- Allison C-4 가 S4 TXM SAE J 306 85W
- Case New Holland MAT - 3525, M2C - 134 A - D, FNHA - 2 - D.201.00
- John Deere JDM - J20C
- Massey - Ferguson M1143, M1145
- Volvo WB 101, Transmission Oil 97303:015
- ZF TE - ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F
- Caterpillar TO - 2 (obsolete)
- Komatsu -
- Dana - Spicer S4 TXM MS 1207, 1209, 1210 Case
- API Gear Performance : API GL - 4

가

Properties		Method	Shell Spirax S4 TXM	
SAE		SAE J 300	10W - 30	
	@40°C	mm ² /s	ISO 3104	60
	@100°C	mm ² /s	ISO 3104	9.4
			ISO 2909	138
	@15°C	kg/m ³	ISO 12185	882
(COC)		°C	ISO 2592	220
		°C	ISO 3016	- 42

S4 TXM

MSDS

MSDS <http://www.epc.shell.com/>



Bonhan

Koo